

Models Brief



Cross OS Upgrade: advanced platforms that support interchangeable Windows CE and Linux-based Operating Systems

NEW!	Class	Brand Name	Model Name	CPU	Flash	RAM	Video Output	Max Resolution	Serial Port	USB Ports	Audio Support	Power Over Ethernet	Management Software
Miniature, Plug Form Factor, High-End, DVI-D	Plug PC	WIN CE	CXP-2310	RMI Au 1250, 528 MHz RISC	256MB	128 MB DDR	DVI-D	Up to 1920x1200 px @ 64K (16 bit) colors	N	4	Y	N	Xcalibur Global
			LXP-2310	RMI Au 1250, 528 MHz RISC	256MB	128 MB DDR	DVI-D	Up to 1600x1200 px @ 64K (16 bit) colors					
Desktop Form Factor, High-End, DVI-D+VGA	Xtreme PC	WIN CE	CXN-2321	RMI Au 1250, 528 MHz RISC	256MB	256MB DDR	VGA+DVI-D	Up to 1920x1200 px @ 64K (16 bit) colors	1	3	Y	N	Xcalibur Global
			LXN-2321	RMI Au 1250, 528 MHz RISC	256MB	256MB DDR	VGA+DVI-D	Up to 1920x1200 px @ 64K (16 bit) colors					
Network-Integrated Form Factor, Power-over-Ethernet, High-End, DVI-I Video	Jack PC	LINUX	LXJ-2311	RMI Au 1250, 528 MHz RISC	256MB	128 MB DDR	DVI-I	Up to 1600x1200 px @ 64K (16 bit) colors	N	4	Y	Y	Xcalibur Global
Desktop Form Factor, High-End, DVI-D+VGA, Fiber Optic, SFP Enabled	Xtreme PC	WIN CE	CXN-2321F	RMI Au 1250, 528 MHz RISC	256MB	256MB DDR	VGA+DVI-D	Up to 1920x1200 px @ 64K (16 bit) colors	1	3	Y	N	Xcalibur Global
			LXN-2321F	RMI Au 1250, 528 MHz RISC	256MB	256MB DDR	VGA+DVI-D	Up to 1920x1200 px @ 64K (16 bit) colors					

Chip PC Linux-based Thinx OS™ Highlights:

- Superb in session performance
- Powerful multimedia with Chip PC video redirection(ICA/RDP)
- ICA 11 with Citrix HDX Plug-n-Play (USB redirection)
- Flexible 3rd party application support
- Full management via Policy-based Xcalibur Global management suite
- Login to Active Directory domain from Linux-based devices
- Cross OS upgrade to Win CE 6.0 OS (optional, pending on purchasing Microsoft license/label)




Windows CE 6.0 OS Highlights:

- Superb in session performance
- Small OS footprint (below 25 MB)
- ICA 10 with Citrix HDX MediaStream (multimedia redirection)
- Full management via Policy-based Xcalibur Global management suite
- Microsoft Native RDP 6
- Cross OS upgrade to Linux-based Thinx OS (optional)



Chip PC Thin Client: Windows Embedded Standard 2009



 Class	Brand Name	Model Name	CPU	Flash	RAM	Video Output	Multi Display Support	Max Resolution	Ports	Audio Support	Management Software
Intel Atom-based, Small Foot Print, Powerful Device	EX-PC	XPD-4741	Intel Atom N270 1.6 GHz Dual Thread	2GB DOM	1GB RAM	DVI-I	Y	1920x1200px @ 16M (32 bit) colors	4 USB 1 PS/2	Y	Xcalibur Global MS WDS, Altiris
Intel Atom-based, Small Foot Print, Powerful Device, Wireless Support	EX-PC	XPD-4741W	Intel Atom N270 1.6 GHz Dual Thread	2GB DOM	1GB RAM	DVI-I	Y	1920x1200px @ 16M (32 bit) colors	4 USB 1 PS/2	Y	Xcalibur Global MS WDS, Altiris

Chip PC Thin Clients: Windows CE-based



Class	Brand Name	Model Name	CPU	Flash	RAM	Separate Video Memory	Video Output	Multi Display Support	Max Resolution	Serial Port	USB Ports	Audio Support	Power Over Ethernet	Management Software
Desktop Form Factor, High-End, DVI-D+VGA, Dual Display Support	Xtreme PC	NG 7500	RMI Au 1550, 500 MHz RISC	256MB	128 MB DDR	8 MB	DVI-D+VGA	Dual Display	Single Display: Up to 1920x1200 px (Reduced Blank) @ 64K (16 bit) colors Dual Display: Up to 1024x768 pixels @ 64 K (16 bit) colors	1	3	Y	N	Xcalibur Global
Desktop Form Factor, High-End, DVI-D+VGA, Dual Display Support, Integrated PC/SC PKI Smart Card	Xtreme PC	NG 7552	RMI Au 1550, 500 MHz RISC	256MB	128 MB DDR	8 MB	DVI-D+VGA	Dual Display	Single Display: Up to 1920x1200px (RB) @64K (16 bit) colors. Quad Display: Up to 1024x768 px @ 64 K (16 bit) colors	1	3	Y	N	Xcalibur Global
Desktop Form Factor, High-End, 2xDVI-I, Multi-Display (2-4) Support	Xtreme PC	NG 6600	RMI Au 1550, 500 MHz RISC	64MB	128 MB DDR	16 MB	2 x DVI-I	2-4 Display	Single+Dual Display: Up to 1920x1200px (RB) @64K (16 bit) colors. Quad Display: Up to 1024x768 px @ 64 K (16 bit) colors	N	4	Y	N	Xcalibur Global
Network-Integrated Form Factor, Power-over-Ethernet, High-End, VGA Video	Jack PC	EFI-7800	RMI Au 1550, 500 MHz RISC	256MB	128 MB DDR	8 MB	VGA	N	Up to 1600x1200 px @ 64K (16 bit) colors	N	4	Y	Y	Xcalibur Global
Network-Integrated Form Factor, Power-over-Ethernet, High-End, DVI-I Video, Dual Display Support	Jack PC	EFI-7900	RMI Au 1550, 500 MHz RISC	256MB	128 MB DDR	8 MB	DVI-I	Dual Display	Single Display: Up to 1920x1200 px (Reduced Blank) @ 64K (16 bit) colors Dual Display: Up to 1024x768 pixels @ 64 K (16 bit) colors	N	4	Y	Y	Xcalibur Global

Making IT a Complete Solution



Rev: 4.4
Date: 05.10

www.chippc.com

Chip PC HQ
+972 (0) 4 850 11 21
info@chippc.com

Chip PC UK
+44 (0) 870 606 1007
info@chippc.co.uk

Chip PC France
+33 (0) 611 4207 84
info.fr@chippc.com

Chip PC Germany
+49 (0) 201 4389 05-0
info@chippc.de

Chip PC US
+1 972 827 0379
+1 866 674 1678
info.us@chippc.com

Notes: (1) To ensure compatibility with Chip PC thin clients, use only power supply and accessories supplied by Chip PC.

(2) Actual display support is dependent on display hardware and cable quality; some of the resolutions and display modes described above may not be supported by certain displays or cables.

© Chip PC Technologies, all rights reserved. Subject to change without prior notice. Images for demonstration purposes only.